


DMHA2


Acoplamento flexível




Diâmetro nominal mm/pol	Diâmetro externo mm/pol	Pressão de trabalho MPa/psi	Dimensões mm			Parafuso Porca
			A	B	C	
25	33,7	2,07	98	58	45	2-M10*50
1	1,327	300				
32	42,4	2,07	106	68	45	2-M10*50
1¼	1,66	300				
40	48,3	2,07	112	73	45	2-M10*50
1½	1,9	300				
50	60,3	2,07	128	86	45	2-M10*55
2	2,375	300				
65	73	2,07	138	98	45	2-M10*55
2½	2,875	300				
65	76,1	2,07	139	99	45	2-M10*55
2½	3	300				
80	88,9	2,07	158	112	45	2-M10*60
3	3,5	300				
100	114,3	2,07	192	143	50	2-M12*70
4	4,5	300				
125	139,7	2,07	223	169	50	2-M12*75
5	5,5	300				
125	141,3	2,07	223	169	50	2-M12*75
5	5,563	300				
150	165,1	2,07	252	198	50	2-M12*75
6	6,5	300				
150	168,3	2,07	252	198	50	2-M12*75
6	6,625	300				
200	216,3	2,07	322	252	60	2-M16*90
8	8,516	300				
200	219,1	2,07	322	254	58	2-M16*90
8	8,625	300				
250	267,4	2,07	384	309	62	2-M20*100
10	10,528	300				
250	273	2,07	388	314	62	2-M20*110
10	10,75	300				
300	318,5	2,07	440	362	62	2-M20*110
12	12,539	300				
300	323,9	2,07	443	365	62	2-M20*110
12	12,75	300				
350	355,6	2,07	460	416	72	3-M22*110
14	14	300				
350	377	2,07	485	441	72	3-M22*110
14	14,85	300				
400	406,1	2,07	512	468	72	3-M22*110
16	16	300				
400	426	2,07	534	490	72	3-M22*110
16	16,77	300				
450	457,2	2,07	569	524	75	3-M22*110
18	18	300				
450	480	2,07	630	533	78	3-M22*110
18	18,898	300				
500	508	2,07	660	576	78	4-M22*110
20	20	300				
500	530	2,07	700	595	78	4-M22*110
20	20,866	300				
600	609,6	2,07	784	680	78	4-M22*110
24	24	300				
600	630	2,07	796	692	78	4-M22*110
24	24,8	300				



1" (33.7mm)-12" (323.9mm)



14" (355.6mm)-18" (480mm)



20" (508mm)-24" (630mm)