


DMHA2H


Acoplamento flexível - alta pressão




Diâmetro nominal mm/pol	Diâmetro externo mm/pol	Pressão de trabalho MPa/psi	Dimensões mm			Parafuso Porca
			A	B	C	
25	33,7	3,45	98	58	45	2-M10*50
1	1,327	500				
32	42,4	3,45	106	68	45	2-M10*50
1¼	1,66	500				
40	48,3	3,45	112	73	45	2-M10*50
1½	1,9	500				
50	60,3	3,45	128	89	45	2-M10*55
2	2,375	500				
65	73	3,45	138	96	45	2-M10*55
2½	2,875	500				
65	76,1	3,45	139	102	45	2-M10*55
2½	3	500				
80	88,9	3,45	158	116	45	2-M10*60
3	3,5	500				
100	114,3	3,45	192	146	50	2-M12*75
4	4,5	500				
125	139,7	3,45	223	172	50	2-M12*75
5	5,5	500				
125	141,3	3,45	223	172	50	2-M12*75
5	5,563	500				
150	159	3,45	260	196	50	2-M16*90
6	6,26	500				
150	165,1	3,45	264	202	50	2-M16*90
6	6,5	500				
150	168,3	3,45	266	206	50	2-M16*90
6	6,625	500				
200	216,3	3,45	322	258	60	2-M16*90
8	8,516	500				
200	219,1	3,45	326	263	60	2-M16*90
8	8,625	500				
250	267,4	3,45	384	309	62	2-M20*110
10	10,528	500				
250	273	3,45	388	314	62	2-M20*110
10	10,75	500				
300	318,5	3,45	440	362	62	2-M20*110
12	12,539	500				
300	323,9	3,45	452	370	64	2-M20*130
12	12,75	500				



1" (33.7mm)-12" (323.9mm)



1½" (38.1mm)-18" (457mm)



2" (50.8mm)-24" (610mm)