

DMHC12

Curva de redução 90° | rosca



Diâmetro nominal mm/pol	Diâmetro externo mm/pol	Pressão de trabalho MPa/psi	Dimensões mm	
			L	
25*15	33,7*21,3	2,07	44	48
1*½	1,327*0,825	300		
25*20	33,7*26,7	2,07	44	48
1*¾	1,327*1,05	300		
32*15	42,4*21,3	2,07	46	48
1¼*½	1,66*0,825	300		
32*20	42,4*26,7	2,07	46	48
1¼*¾	1,66*1,05	300		
32*25	42,4*1	2,07	51	52
1¼*1	1,66*1,327	300		
40*15	48,3*21,3	2,07	46	48
1½*½	1,90*0,825	300		
40*20	48,3*26,7	2,07	46	48
1½*¾	1,9*1,05	300		
40*25	48,3*33,7	2,07	51	52
1½*1	1,9*1,327	300		
50*15	60,3*21,3	2,07	48	48
2*½	2,375*0,825	300		
50*20	60,3*26,7	2,07	48	48
2*¾	2,375*1,05	300		
50*25	60,3*33,7	2,07	51	52
2*1	2,375*1,327	300		
65*15	73*21,3	2,07	58	48
2½*½	2,875*0,825	300		
65*20	73*26,77	2,07	58	48
2½*¾	2,875*1,05	300		
65*25	73*33,7	2,07	65	55
2½*1	2,875*1,327	300		
65*15	76,1*21,3	2,07	58	48
2½*½	3*0,825	300		
65*20	76,1*26,7	2,07	58	48
2½*¾	3*1,05	300		
65*25	76,1*33,7	2,07	65	55
2½*1	3*1,327	300		

