

DMHCA1

Cap ranhurado



Diâmetro nominal mm/pol	Diâmetro externo mm/pol	Pressão de trabalho MPa/psi	Dimensões mm
			L
25	33,7	2,07	25
1	1,327	300	
32	42,4	2,07	25
1¼	1,66	300	
40	48,3	2,07	25
1½	1,9	300	
50	60,3	2,07	25
2	2,375	300	
65	73	2,07	25
2½	2,875	300	
65	76,1	2,07	25
2½	3	300	
80	88,9	2,07	25
3	3,5	300	
100	108	2,07	28
4	4,252	300	
100	114,3	2,07	28
4	4,5	300	
125	133	2,07	28
5	5,25	300	
125	139,7	2,07	28
5	5,5	300	
125	141,3	2,07	28
5	5,563	300	
150	159	2,07	28
6	6,26	300	
150	165,1	2,07	28
6	6,5	300	
150	168,3	2,07	28
6	6,625	300	
200	216,3	2,07	32
8	8,516	300	
200	219,1	2,07	32
8	8,625	300	
250	267,4	2,07	34
10	10,528	300	
250	273	2,07	34
10	10,75	300	
300	318,5	2,07	34
12	12,539	300	
300	323,9	2,07	34
12	12,75	300	
350	355,6	2,07	102
14	14	300	
350	377	2,07	102
14	14,84	300	
400	406,4	2,07	102
16	16	300	
400	426	2,07	102
16	16,77	300	
450	457,2	2,07	127
18	18	300	
450	480	2,07	127
18	18,9	300	
500	508	2,07	152
20	20	300	
600	609,6	2,07	152
24	24	300	

